



MODEL 1500B / 1520E SELF-PROPELLED CARPET EXTRACTOR SPECIFICATIONS



Vacuum System

Cleaning path	22 in	559 mm
Vacuum motor	1 hp – B/1.9 hp -E	29 A – B 12.9 A - E
Vacuum motor stages	2-stage B/3-stage - E	2-stage B/3-stage - E
Waterlift	81in – B/120 in - E	2057mm – B/3048 mm -E
Airflow	88 cfm	2.49 cmm
Recovery tank capacity	17 gal	64 L
Productivity (per hour)	4500ft ²	418 m ²

Solution & Brush System

Solution tank capacity	17 gal (B) / 27 gal (E)	64L – B/102L - E
Solution flow	1 gal / min	3.8 L / min
Spray jets	6	6
Pump pressure	100 psi	7 bar
Coverage rate per tank	1435 ft ²	133 m ²
Brush rpm	1200 rpm	1200 rpm
Brush motor	.12 hp	.12 hp

Total Power Consumption

Batteries / Cord	2 (12 V) – 1500B / 75 ft	2 (12 V) – 1500B / 23 m
Amps	50 A (B) / 12. 7 A (E)	50 A (B) / 12.7 A (E)
Voltage	24 V (B) / 120 V (E)	24 V (B) / 120 V (E)

Body Construction

Chassis	Polyethylene	polyethylene
---------	--------------	--------------

Optional Accessories

- Hand tool
- Solution hose extension
- Floor tools
- Upholstery tool
- Vacuum hose
- Floor wand