



T15 Specifications

INDUSTRIAL RIDING SCRUBBER WITH ec-H2O™ converted water scrubbing technology FaST® foam scrubbing technology

Feature		
Scrubbing System		
Cleaning path	36-inch	910 mm
Scrub head offset	2-inch	50 mm
Solution tank	45 gallon	170 liter
Productivity (per hour)		
Theoretical max	95,040 ft ² /hr	9,100 m ² /hr
Estimated Coverage* (Conventional)	26,700 ft ² /hr	2,462 m ² /hr
Estimated Coverage* (ec-H2O™)	42,134 ft ² /hr	3,888 m ² /hr
Estimated Coverage* (FaST®)	42,134 ft ² /hr	3,888 m ² /hr
Disk scrub head		
Speed	320 rpm	320 rpm
Down pressure weight (variable to)	200 lb	91 kg
Brush diameter (2)	18-inch	460 mm
Brush motor (2)	0.75 hp	0.56 kW
Cylindrical scrub head		
Speed	750 rpm	750 rpm
Down pressure weight (variable to)	90 lb	40 kg
Brush diameter (2)	6-inch	150 mm
Brush motor (2)	0.75 hp	0.56 kW
Recovery System		
Recovery tank	55 gallon	208 liter
Demisting chamber	10 gallon	38 liter
Vacuum fan speed	14,000 rpm	14,000 rpm
Vacuum water lift	70-inch	1,780 mm
Vacuum fans (2)	0.8 hp	0.6 kW
Propelling System		
Propel speed forward (variable to)	6.0 mph	10 km/h
Propel speed reverse (variable to)	2.5 mph	4.0 km/h
Propel motor	1.5 hp	1.1 kW
Gradeability		
Transport at gross weight	8.0 deg/14.1%	8.0 deg/14.1%
Working (scrubbing)	4.0 deg/7.0%	4.0 deg/7.0%
Machine Dimensions		
Length	72-inch	1,830 mm
Width	40.25-inch	1,020 mm
Rear squeegee	45.5-inch	1,160 mm
Height	53.5-inch	1,360 mm
With overhead guard	80-inch	2,030 mm
Weight	1,105 lb	501 kg
With standard 235 Ah battery	1,505 lb	680 kg
Minimum aisle turn	82-inch	2,080 mm
Warranty	Please refer to your local Tennant representative for information.	

Underwriter's Laboratory (UL®) E certified

ec-H2O™ is certified to provide high traction by the National Floor & Safety Institute

